



M-250 Ultra Monoblock Amplifiers

Elegant and refined, yet brutally powerful, Rogue Audio's flagship monoblock amplifiers have raised the bar for reference level amplification. The M-250's ability to reveal the finest musical details while providing seemingly limitless dynamics are the hallmark of the finest amplifiers we have ever produced. Whether your passion is jazz, rock or symphonic works, these amplifiers will provide the clarity and dynamics to closely rival the original performance.

That these pure tube amplifiers boast a continuous power output of over 250 watts is but a small part of the story. Designed and engineered without compromise, the M-250s boast ruler flat frequency response, tremendous bandwidth, huge dynamic range, and vanishingly low levels of distortion. The enormous linear power supplies enable the reproduction of musical transients at far beyond the amplifier's rated output. The ultra-high tolerance components and huge transformers contribute to the peerless build quality. Features include an on-the-fly switch offering either Triode or Ultralinear operation. A built in meter and individual bias switches makes tube biasing a snap even for the tube novice. The rear panel contains balanced and single ended inputs as well as 4 and 8 ohm binding posts.

General Features:

- Monoblock design for perfect channel separation
- Massive high storage linear power supply
- Ultra-high performance transformers
- Built in bias meters
- All precision components
- 6 x KT88, 2 x 12AU7, 1 x 12AX7 tubes per amp
- Heavy-duty rhodium plated RCA connectors
- Heavy-duty rhodium plated binding posts
- Balanced (XLR) and RCA inputs
- Both 4 and 8 ohm binding posts
- User selectable triode/ultralinear output
- Fully tested, burned-in, and auditioned
- Entirely designed and built in the USA

Specifications:

- Output power: 250 WPC in Ultralinear Mode with KT-88s
- THD: less than 0.1% typical, 1% at peak
- frequency response:
- 20Hz -25KHz at full output
- 10Hz -75KHz
- Input sensitivity: 1.0V RMS
- Dimensions: 12.75" W x 18" D x 13" H
- Weight: 88 lbs each
- Power requirements: 115V/230V – 50/60Hz

